





PC工程塑料紧固件 聚碳酸酯(Polycarbonate)

●该材料为非结晶性工程塑料。具有超群的抗冲击强度、机械性能和电特性综合优异，被广泛用于于电气、电子、医疗、汽车等领域。

●连续使用温度115℃ ●燃烧性UL94 V-2

图片	名称 (编号)	规格									
		M1.7	M2	M2.6	M3	M4	M5	M6	M8		
	盘头螺丝 (PC/PH)	M1.7	M2	M2.6	M3	M4	M5	M6	M8		
	节距	0.35	0.4	0.45	0.5	0.7	0.8	1	1.25		
	长度										
	3	○	○	○							
	4	○	○	○	○						
	5		○	○	○	○					
	6		○	○	○	○	○				
	8		○	○	○	○	○				
	10		○	○	○	○	○	○			
	12		○	○	○	○	○	○	○		
	15			○	○	○	○	○	○	○	
	16				○	○	○				
	18				○	○	○				
	20				○	○	○	○	○		
	25				○	○	○	○	○		
	30				○	○	○	○	○		
	35						○	○			
40					○		○	○			
	埋头螺丝 (PC/FH)	M1.7	M2	M2.6	M3	M4	M5	M6	M8		
	节距	0.35	0.4	0.45	0.5	0.7	0.8	1	1.25		
	长度										
	4		○	○	○						
	5		○	○	○						
	6		○	○	○	○					
	8		○	○	○	○	○				
	10		○	○	○	○	○	○	○		
	12			○	○	○	○	○	○		
	14					○					
	15				○	○	○	○	○		
	16				○	○					
	18				○	○					
	20				○	○	○	○	○		
	25				○	○	○	○	○		
	30							○	○		
	35							○			
	沉头螺丝 (PC/OH)	M1.7	M2	M2.6	M3	M4	M5	M6	M8		
	节距	0.35	0.4	0.45	0.5	0.7	0.8	1	1.25		
	长度										
	5				○						
	6				○						
	8				○						
	10				○	○					
	12				○	○					
	15				○	○					
20				○	○						
25					○						
	螺丝 (PC/SS)	M1.7	M2	M2.6	M3	M4	M5	M6	M8		
	节距	0.35	0.4	0.45	0.5	0.7	0.8	1	1.25		
	长度										
	4				○						
6					○		○				